MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ACRY-SHEEN SATIN ENAMEL 50 VOC HMIS CODES: H F R P

PRODUCT CODE: CAEX-7200

======== SECTION I - MANUFACTURER IDENTIFICATION ============

MANUFACTURER'S NAME: Scotch Paint

ADDRESS: 555 WEST 189TH STREET, GARDENA, CALIFORNIA 90248

EMERGENCY PHONE: 310-329-1259 **INFORMATION PHONE:** 310-329-1259

DATE REVISED : 12-31-13 NAME OF PREPARER: RJN

====== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =======

		OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE	WEIGHT
HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL	ACGIH TLV	OTHER	mm Hg @ TEMP	PERCENT
PROPYLENE GLYCOL	57-55-6	N/A	N/A	N/A	n/A	< 5.0%
SILICON DIOXIDE/AMORPHOUS, MICROCRYSTALLINE SILICA	14808-60-7	0.1Mg/M3	0.1Mg/M3	N/A	N/A	< 0.5%
2,2.4-TRIMETHYLPENTANEDIOL-1,3-MONOISOBUTYRATE	25265-77-4	NE	NE	NE	1.0 189F	< 5.0%

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. *** FOLLOW ALL LABEL DIRECTIONS.WARNING THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND /OR BIRTH DEFECTS OR REPRODUCTIVE HARM. COMPLIES WITH TITLE 8 CALIFORNIA CODE OF REGULATIONS SECTION 5194.

======= SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =========

BOILING RANGE: 369 to 471 Deg F SPECIFIC GRAVITY (H20=1):
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER

COATING V.O.C.: 0.40 LB/GL (48 G/L)

SOLUBILITY IN WATER: VEHICLE PORTION COMPLETE

APPEARANCE AND ODOR: SLIGHT AMMONIA

======== SECTION IV - FIRE AND EXPLOSION HAZARD DATA ==========

METHOD USED: N/A FLASH POINT: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.6% UPPER: 12.5%

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

SELF CONTAINED BREATHING APPARATUS RECOMENDED. COMBUSTION PRODUCES CO, CO2

UNUSUAL FIRE AND EXPLOSION HAZARDS

CAEX-7200 MATERIAL SAFETY DATA SHEET

PAGE 2 OF 3

STABILITY: STABLE CONDITIONS TO AVOID

EXCESS HEAT, STRONG ACIDS OR ALKALIS

INCOMPATIBILITY (MATERIALS TO AVOID)

UNKNOWN

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

CO, CO2 ON COMBUSTION

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NAUSEA, DIZZYNESS, DROUSINESS, WEAKNESS, HEADACHE.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

RASH, BURNING, SWELLING, ITCHING, WATERING EYES.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

RASH, SWELLING, ITCHING, REDNESS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NAUSEA, CRAMPS, HEADACHE

HEALTH HAZARDS (ACUTE AND CHRONIC)

UNKNOWN

CARCINGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

UNKNOWN

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

UNKNOWN

EMERGENCY AND FIRST AID PROCEDURES

INHALATION REMOVE TO FRESH AIR.IF UNCONSIOUS CALL PHYSICIAN IMMEDIATLY. INGESTION DO NOT INDUCE VOMITING CALL PHYSICIAN IMMEDIATLY.

SKIN CONTACT WASH WELL WITH SOAP AND WATER.IF RASH DEVELOPES CONSULT PHYSICIAN

EYE CONTACT FLUSH WITH COPIOUS AMOUNT OF WATER CONSULT PHYSICIAN.

====== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WIPE UP SMALL SPILLS WITH ABSORBANT RAGS OR TOWELS LARGE SPILLS DIKE AREA AND PUMP INTO DRUMS FOR RECOVERY OR DISPOSAL

WASTE DISPOSAL METHOD

FOLLOW FEDERAL STATE AND LOCAL REGULATIONS REGARDING PROPER DISPOSAL OF PAINT AND RELATED MATERIALS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

WEAR APPROVED ORGANIC VAPOR RESPIRATOR UNLESS ADEQUATE VENTALATION EQUIPMENT IS AVAILABLE TO KEEP ORGANIC VAPOR BELOW TL

OTHER PRECAUTIONS

KEEP CONTAINERS CLOSED WHEN NOT IN USE KEEP FROM OPEN FLAMES OR EXCESS HEAT STORE IN COOL DRY PLACES. DO NOT FREEZE
KEEP OUT OF REACH OF CHILDREN

RESPIRATORY PROTECTION

WEAR APPROVED RESPIRATOR FOR DUST AND ORGANIC VAPORS.

VENTILATION

OPEN WINDOWS AND DOORS GENERALY ARE SUFFICENT TO KEEP TLV BELOW HAZZARDOUS CONCENTRATIONS IF NOT EMPLOY MECHANICAL VENTALATION EQUIPMENT TO KEEP BELOW TLV OF PRODUCT

PROTECTIVE GLOVES

USE NEOPRENE RUBBER GLOVES TO PROTECT AGAINST SKIN EXPOSURE

EYE PROTECTION

WEAR SPLASH RESISTANT GOGGLES TO PROTECT EYES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NEOPRENE RUBBER APRON RECOMENDED WHEN USING THIS PRODUCT. WEAR HAT TO PROTECT SCALP FROM THIS PRODUCT.

WORK/HYGIENIC PRACTICES

EMERGENCY EYE WASH AND SAFTEY SHOWERS RECOMENDED.

WASH HANDS BEFORE EATING OR SMOKING.

DISCLAIMER

THE INFORMATION CONTAINED HEARIN IS FURNISHED WITHOUT WARRANTY OF ANY KIND INFORMATION FURNISHED IS BELIEVED TO BE CORRECT. ANY USE OF THIS INFORMATION MUST BE VERIFIED BY INDEPENDENT DETERMINATION OF SUITABILITY AND COMPLETENESS.